



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SCCL

**SUPER PREMIUM SYNTHETIC
COMPRESSOR FLUID**

American Synthol, Inc.

2930 Mountain Trace
Roswell, GA 30075
Phone: 800-633-5457
Fax: 888-731-9534

AMERILUBE SCCL

AMERILUBE SCCL synthetic centrifugal compressor lubricant is super premium, high performance product designed specifically for today's bull gear type centrifugal compressors. This fluid provides outstanding thermal and oxidative stability.

AMERILUBE SCCL has exceptional anti-wear, rust, and corrosion protection. It is extremely shear stable, and is formulated to control oil misting, so common in these compressors. AMERILUBE SCCL is a very long life fluid designed to give years of trouble free service.

- Outstanding Oxidation Stability
- High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Reduced Misting
- Exceeds All Centrifugal OEM Specifications
- Long Fluid Life
- Excellent Rust & Corrosion Protection
- Carbon and Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Compatible with All Seal Materials

Typical Properties

Lubricant Designation	SCCL-32	SCCL-46
Viscosity Index	135	132
Vis cSt @ 40 °C	33	43
Vis cSt @ 100 °C	6.1	7.2
Vis SUS @ 100 °F	155.0	200.1
Vis SUS @ 212 °F	46.2	49.4
Flash Point °F	455	475
Auto-Ignition Point °F	745	770
Pour Point °F	-44	-40
Four Ball, 40 Kg, 1200 RPM, 167 °F 1 Hr, Scar Dia mm	.40	.40
Four Ball Weld point, Kg	100	100
Copper Corrosion, 24 Hr.	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0