



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SERIES DE

SUPER PREMIUM SYNTHETIC
COMPRESSOR FLUIDS

American Synthol, Inc.

2930 Mountain Trace
Roswell, GA 30075
Phone: 800-633-5457
Fax: 888-731-9534

AMERILUBE SERIES DE

AMERILUBE SERIES DE compressor lubricants are super premium, 100% synthetic diester base with an advanced technology additive system. They are blended from the finest materials available. Proven in countless millions of horsepower hours of service in virtually every type of compressor made. AMERILUBE SERIES DE lubricants give outstanding service, even in the most severe operating conditions.

- Outstanding Oxidation Stability
- High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Excellent Dispersant Properties
- Long Fluid Life
- Excellent Rust Control
- Carbon and Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption

Typical Properties

Lubricant Designation	A 320C	A 460C	A 680C	A 1000C	A 1500C
Viscosity Index	81	79	86	93	92
Viscosity cSt @ 40 °C	33	39	64	108	146
Viscosity cSt @ 100 °C	5.2	5.7	7.9	11.5	14.1
Viscosity SUS @ 100 °F	155	182	297	500	685.7
Viscosity SUS @ 212 °F	43.3	44.9	52	64.6	74.4
Flash Point °F	420	450	480	485	502
Auto-Ignition Point °F	765	785	790	835	835
Pour Point °F	-45	-45	-45	-35	-30
Four Ball, 40 Kg, 1200 RPM, 167°F					
1 Hr, Scar Dia mm	.40	.40	.40	.40	.40
Four Ball Weld Point, Kg	100	100	110	125	135
Copper Corrosion, 24 Hr	1a	1a	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/38/2	40/38/2	40/38/2	40/38/2	40/38/2