



# AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

## SBL

**SUPER PREMIUM SYNTHETIC  
BLOWER FLUID**

American Synthol, Inc.

2930 Mountain Trace  
Roswell, GA 30075  
Phone: 800-633-5457  
Fax: 888-731-9534

## AMERILUBE SBL

AMERILUBE SYNTHETIC BLOWER LUBRICANTS are blended from the highest quality base stocks available. They are blended with AMERILUBE's most advanced additive system, and are designed specifically for the gears and bearings in rotary lobe blowers. They exhibit outstanding resistance to oxidation, shear, and thermal degradation. These lubricants have excellent lubricity and anti-wear properties.

AMERILUBE SYNTHETIC BLOWER LUBRICANTS provide excellent protection against rust and corrosion. They also provide unusual protection from foaming and air entrainment. They are designed to provide maximum protection in all types of rotary lobe blowers.

- Excellent Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto Ignition Points
- Very Low Volatility
- Excellent Film Strength
- Excellent Coolant Properties
- Good Dispersant Properties
- Very Long Fluid Life
- Excellent Rust Control
- Excellent Sludge and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption
- Excellent Water Separation

## Typical Properties

Lubricant Designation	SBL-220
Viscosity Index	171
AGMA Number	5
Vis cSt @ 40 °C	200.1
Vis cSt @ 100 °C	27.0
Vis SUS @ 100 °F	927.0
Vis SUS @ 212 °F	129.0
Flash Point °F	515
Auto-Ignition Point °F	790
Pour Point °F	-45
Timken "OK" Load Lb.	65
Copper Corrosion, 24 Hr.	1a
Rust Test	PASS
Demulsibility, 130 °F, 30 min	40/40/0
Four Ball Weld, Kg	170
Four Ball Scar Dia	.40