



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SERIES 5

SUPER PREMIUM SYNTHETIC
COMPRESSOR FLUIDS

American Synthol, Inc.

2930 Mountain Trace
Roswell, GA 30075
Phone: 800-633-5457
Fax: 888-731-9534

AMERILUBE SERIES 5

AMERILUBE SERIES 5 compressor lubricants are 100% synthetic advanced technology lubricants. They are blended from the finest materials available, and are formulated to give outstanding performance under severe conditions. They are compatible with virtually all materials including polycarbonate.

- Outstanding Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Very Long Life Fluid
- Energy Savings
- Carbon and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Excellent Materials Compatibility
- Reduced Lubricant Consumption
- Excellent Rust & Corrosion Control

Typical Properties

Lubricant Designation	A465C	A685C	A1550C
Viscosity Index	136	138	157
Viscosity cSt @ 40 °C	46.7	66.3	92.8
Viscosity cSt @ 100 °C	7.81	10.0	14.1
Viscosity SUS @ 100 °F	217.4	307.6	430.1
Viscosity SUS @ 212 °F	51.8	59.2	74.4
Flash Point °F	490	504	510
Auto-Ignition Point °F	760	760	780
Pour Point °F	-60	-55	-55
Four Ball, 40 Kg, 1200 RPM, 167°F 1 Hr, Scar Dia mm	.45	.45	.37
Four Ball Weld Point, Kg	100	110	125
Copper Corrosion, 24 Hr	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/0