



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

SERIES 7

SUPER PREMIUM SYNTHETIC
COMPRESSOR FLUIDS

American Synthol, Inc.

2930 Mountain Trace
Roswell, GA 30075
Phone: 800-633-5457
Fax: 888-731-9534

AMERILUBE SERIES 7

AMERILUBE SERIES 7 compressor lubricants represent American Synthol's continued leadership in producing exceptional performance compressor fluids. These are blended from several synthetic base stocks, have a new advanced technology additive system, and provide outstanding performance. AMERILUBE SERIES 7 lubricants combine the best characteristics of these base stocks to form a synergistic blend of fluid and additive systems.

- Outstanding Oxidation Stability
- Very High Viscosity Index
- High Flash & Auto-Ignition Points
- Very Low Volatility
- Extremely High Film Strength
- Excellent Coolant Properties
- Very Long Life Fluid
- Energy Savings
- Carbon and Varnish Control
- Reduced Maintenance Costs
- Reduced Downtime
- Excellent Materials Compatibility
- Reduced Lubricant Consumption
- Excellent Rust & Corrosion Control

Typical Properties

Lubricant Designation	A 327C	A 467C	A 687C
Viscosity Index	128	130	131
Viscosity cSt @ 40 °C	34	49	69.8
Viscosity cSt @ 100 °C	6.1	7.9	10.2
Viscosity SUS @ 100 °F	159.0	228	323.8
Viscosity SUS @ 212 °F	45.9	52.0	59.9
Flash Point °F	440	450	498
Auto-Ignition Point °F	735	785	790
Pour Point °F	-48	-38	-32
Four Ball, 40 Kg, 1200 RPM, 167°F			
1 Hr, Scar Dia mm	.40	.40	.40
Four Ball Weld Point, Kg	100	100	110
Copper Corrosion, 24 Hr	1a	1a	1a
Demulsibility, 130 °F, 30 min	40/40/0	40/40/0	40/40/0