



AMERILUBE

ADVANCED TECHNOLOGY LUBRICANTS

ATP-FG

SUPER PREMIUM SYNTHETIC FOOD
GRADE AIR TOOL PROTECTOR

American Synthol, Inc.

2930 Mountain Trace
Roswell, GA 30075
Phone: 800-633-5457
Fax: 888-731-9534

AMERILUBE ATP-FG

AMERILUBE ATP-FG - Air Tool Protector Food Grade is a super premium, synthetic food grade air tool lubricant. It is made from advance technology synthetic food grade base stock and FDA H-1 approved additives to provide maximum lubrication, cleaning, and protection for modern air tools where incidental food contact is possible.

AMERILUBE ATP-FG - Air Tool Protector Food Grade removes deposits and cleans stuck air tools. It provides outstanding service in even the most severe operating conditions.

AMERILUBE ATP-FG meets FDA H-1 (21 CFR 178.3570), and is recommended for applications where incidental food contact is possible.

- Outstanding Oxidation Stability
- Unsurpassed Water Separation
- High Flash & Auto-Ignition Points
- Low Volatility
- Very High Film Strength
- Excellent Coolant Properties
- Excellent Cleaning Properties
- Superior Penetrating Ability
- Excellent Rust Control
- Carbon and Varnish Control
- Energy Savings
- Reduced Maintenance Costs
- Reduced Downtime
- Reduced Lubricant Consumption

Typical Properties

Lubricant Designation	ATP-FG
Viscosity Index	127
Viscosity cSt @ 40 °C	22.1
Viscosity cSt @ 100 °C	4.6
Viscosity SUS @ 100 °F	106.3
Viscosity SUS @ 212 °F	41.4
Flash Point °F	315
Auto-Ignition Point °F	655
Pour Point °F	-20
Oxidation Stability	10000
Color	<.5
Copper Corrosion, 24 Hr	1a
Rust Test	No Rust
Demulsibility, 130 °F, 30 min	40/40/0