



Air flow at nominal condition <sup>1</sup>	13000 l/min - 780 m <sup>3</sup> /h - 459 Scfm
Pressure DewPoint at nominal condition <sup>1</sup>	5 °C
Nominal ambient temperature	25 °C
Max. ambient temperature	45 °C
Min. ambient temperature	1 °C
Nominal inlet air temperature	35 °C
Max. inlet air temperature	55 °C
Nominal inlet air pressure	7 barg
Max. inlet air pressure	14 barg
Max. outlet air pressure drop - Δp	0.20 bar
Inlet-outlet air connection	G 2" BSP – F
Refrigerant type and quantity	R404A – 1.30 kg
Cooling air flow	1900 m <sup>3</sup> /h
Power supply	1/230V/50Hz
Nominal electric consumption	1550 W – 7.4 A
Max. electric consumption	2100 W – 9.8 A
Max. noise level at 1m	< 70 dbA
Weight net - gross	96 – 109 kg

<sup>1</sup> The nominal condition refers to an ambient temperature of +25°C with inlet air at 7barg and 35°C.

Correction factor for operating pressure changes :									
Inlet air pressure	barg	4	5	6	7	8	10	12	14
Correction factor		0.77	0.86	0.93	1.00	1.05	1.14	1.21	1.27
Correction factor for ambient temperature changes :									
Ambient temperature	°C	25	30	35	40	45			
Correction factor		1.00	0.98	0.95	0.88	0.80			
Correction factor for inlet air temperature changes :									
Air temperature	°C	30	35	40	45	50	55		
Correction factor		1.15	1.00	0.84	0.71	0.59	0.50		
Correction factor for DewPoint changes :									
DewPoint	°C	3	5	7	10				
Correction factor		0.91	1.00	1.10	1.26				